



# ISO Standards Handbook:

## Fasteners and screw threads

Volume 2: Product standards

1998, Ed. 4, 480 p., ISBN 92-67-10272-9

## Contents

### Part 3 : Product standards

#### 3.1 External drive hexagon head bolts and screws

<b>ISO 4014:1988</b>	Hexagon head bolts — Product grades A and B
<b>ISO 4015:1979</b>	Hexagon head bolts — Product grade B — Reduced shank (shank diameter approximately equal to pitch diameter)
<b>ISO 4016:1988</b>	Hexagon head bolts — Product grade C
<b>ISO 4017:1988</b>	Hexagon head screws — Product grades A and B
<b>ISO 4018:1988</b>	Hexagon head screws — Product grade C
<b>ISO 4162:1990</b>	Hexagon flange bolts — Small series
<b>ISO 7411:1984</b>	Hexagon bolts for high-strength structural bolting with large width across flats (thread lengths according to ISO 888) — Product grade C — Property classes 8.8 and 10.9
<b>ISO 7412:1984</b>	Hexagon bolts for high-strength structural bolting with large width across flats (short thread length) — Product grade C — Property classes 8.8 and 10.9
<b>ISO 8676:1988</b>	Hexagon head screws with metric fine pitch thread — Product grades A and B
<b>ISO 8765:1988</b>	Hexagon head bolts with metric fine pitch thread — Product grades A and B

#### 3.2 Square neck bolts

<b>ISO 8677:1986</b>	Cup head square neck bolts with large head — Product grade C
<b>ISO 8678:1988</b>	Cup head square neck bolts with small head and short neck — Product grade B
<b>ISO 10642:1997</b>	Hexagon socket countersunk head screws

### 3.3 Hexagon socket head screws

ISO 4762:1997	Hexagon socket head cap screws
ISO 7379:1983	Hexagon socket head shoulder screws
ISO 7380:1997	Hexagon socket button head screws

### 3.4 Slotted head screws

ISO 1207:1992	Slotted cheese head screws — Product grade A
ISO 1580:1994	Slotted pan head screws — Product grade A
ISO 2009:1994	Slotted countersunk flat head screws (common head style) — Product grade A
ISO 2010:1994	Countersunk slotted raised head screws (common head style) — Product grade A

### 3.5 Cross-recessed head screws

ISO 7045:1994	Pan head screws with type H or type Z cross recess — Product grade A
ISO 7046-1:1994	Countersunk flat head screws (common head style) with type H or type Z cross recess — Product grade A — Part 1: Steel of property class 4.8
ISO 7046-2:1990	Cross-recessed countersunk flat head screws (common head style) — Grade A — Part 2: Steel of property class 8.8, stainless steel and non-ferrous metals
ISO 7047:1994	Countersunk raised head screws (common head style) with type H or type Z cross recess — Product grade A

### 3.6 Set screws

ISO 2342:1972	Slotted headless screws — Metric series
ISO 4026:1993	Hexagon socket set screws with flat point
ISO 4027:1993	Hexagon socket set screws with cone point
ISO 4028:1993	Hexagon socket set screws with dog point
ISO 4029:1993	Hexagon socket set screws with cup point
ISO 4766:1983	Slotted set screws with flat point
ISO 7434:1983	Slotted set screws with cone point
ISO 7435:1983	Slotted set screws with long dog point
ISO 7436:1983	Slotted set screws with cup point

### 3.7 Tapping screws

<b>ISO 1479:1983</b>	Hexagon head tapping screws
<b>ISO 1481:1983</b>	Slotted pan head tapping screws
<b>ISO 1482:1983</b>	Slotted countersunk (flat) head tapping screws (common head style)
<b>ISO 1483:1983</b>	Slotted raised countersunk (oval) head tapping screws (common head style)
<b>ISO 7049:1983</b>	Cross recessed pan head tapping screws
<b>ISO 7050:1983</b>	Cross recessed countersunk (flat) head tapping screws (common head style)
<b>ISO 7051:1983</b>	Cross recessed raised countersunk (oval) head tapping screws
<b>ISO 7053:1992</b>	Hexagon washer head tapping screws
<b>ISO 10509:1992</b>	Hexagon flange head tapping screws

### 3.8 Hexagon nuts

<b>ISO 4032:1986</b>	Hexagon nuts, style 1 — Product grades A and B
<b>ISO 4033:1979</b>	Hexagon nuts, style 2 — Product grades A and B
<b>ISO 4034:1986</b>	Hexagon nuts — Product grade C
<b>ISO 4035:1986</b>	Hexagon thin nuts (chamfered) — Product grades A and B
<b>ISO 4036:1979</b>	Hexagon thin nuts — Product grade B (unchamfered)
<b>ISO 4161:1983</b>	Hexagon nuts with flange — Product grade A
<b>ISO 4166:1979</b>	Hexagon nuts for fine mechanics — Product grade F
<b>ISO 4775:1984</b>	Hexagon nuts for high-strength structural bolting with large width across flats — Product grade B — Property classes 8 and 10
<b>ISO 7413:1984</b>	Hexagon nuts for structural bolting, style 1, hot-dip galvanized (oversize tapped) — Product grades A and B — Property classes 5, 6 and 8
<b>ISO 7414:1984</b>	Hexagon nuts for structural bolting with large width across flats, style 1 — Product grade B — Property class 10
<b>ISO 7417:1984</b>	Hexagon nuts for structural bolting — Style 2, hot-dip galvanized (oversize tapped) — Product grade A — Property class 9
<b>ISO 8673:1988</b>	Hexagon nuts, style 1, with metric fine pitch thread — Product grades A and B
<b>ISO 8674:1988</b>	Hexagon nuts, style 2, with metric fine pitch thread — Product grades A and B
<b>ISO 8675:1988</b>	Hexagon thin nuts with metric fine pitch thread — Product grades A and B

### 3.9 Prevailing torque type nuts

<b>ISO 7040:1997</b>	Prevailing torque type hexagon nuts (with non-metallic insert), style 1 — Property classes 5, 8 and 10
<b>ISO 7041:1997</b>	Prevailing torque type hexagon nuts (with non-metallic insert), style 2 — Property classes 9 and 12
<b>ISO 7042:1997</b>	Prevailing torque type all-metal hexagon nuts, style 2 — Property classes 5, 8, 10 and 12
<b>ISO 7043:1997</b>	Prevailing torque type hexagon nuts with flange (with non-metallic insert) — Product grades A and B
<b>ISO 7044:1997</b>	Prevailing torque type all-metal hexagon nuts with flange — Product grades A and B
<b>ISO 7719:1997</b>	Prevailing torque type all-metal hexagon nuts, style 1 — Property classes 5, 8 and 10
<b>ISO 7720:1997</b>	Prevailing torque type all-metal hexagon nuts, style 2 — Property class 9
<b>ISO 10511:1997</b>	Prevailing torque type hexagon thin nuts (with non-metallic insert)
<b>ISO 10512:1997</b>	Prevailing torque type hexagon nuts (with non-metallic insert), style 1, with metric fine pitch thread — Property classes 6, 8 and 10
<b>ISO 10513:1997</b>	Prevailing torque type all-metal hexagon nuts, style 2, with metric fine pitch thread — Property classes 8, 10 and 12
<b>ISO 12125:1997</b>	Prevailing torque type hexagon nuts with flange (with non-metallic insert) with metric fine pitch thread — Product grades A and B
<b>ISO 12126:1997</b>	Prevailing torque type all-metal hexagon nuts with flange with metric fine pitch thread — Product grades A and B

### 3.10 Washers

<b>ISO 887:1983</b>	Plain washers for metric bolts, screws and nuts — General plan
<b>ISO 7089:1983</b>	Plain washers — Normal series — Product grade A
<b>ISO 7090:1983</b>	Plain washers, chamfered — Normal series — Product grade A
<b>ISO 7091:1983</b>	Plain washers — Normal series — Product grade C
<b>ISO 7092:1983</b>	Plain washers — Small series — Product grade A
<b>ISO 7093:1983</b>	Plain washers — Large series — Product grades A and C
<b>ISO 7094:1983</b>	Plain washers — Extra large series — Product grade C
<b>ISO 7415:1984</b>	Plain washers for high-strength structural bolting, hardened and tempered
<b>ISO 7416:1984</b>	Plain washers, chamfered, hardened and tempered for high-strength structural bolting
<b>ISO 8738:1986</b>	Plain washers for clevis pins — Product grade A

### 3.11 Pins

<b>ISO 1234:1997</b>	Split pins
<b>ISO 2338:1997</b>	Parallel pins, of unhardened steel and austenitic stainless steel
<b>ISO 2339:1986</b>	Taper pins, unhardened
<b>ISO 2340:1986</b>	Clevis pins without head
<b>ISO 2341:1986</b>	Clevis pins with head
<b>ISO 8733:1997</b>	Parallel pins with internal thread of unhardened steel and austenitic stainless steel
<b>ISO 8734:1997</b>	Parallel pins of hardened steel and martensitic stainless steel (Dowel pins)
<b>ISO 8735:1997</b>	Parallel pins with internal thread of hardened steel and martensitic stainless steel
<b>ISO 8736:1986</b>	Taper pins with internal thread, unhardened
<b>ISO 8737:1986</b>	Taper pins with external thread, unhardened
<b>ISO 8739:1997</b>	Grooved pins — Full-length parallel grooved, with pilot
<b>ISO 8740:1997</b>	Grooved pins — Full length parallel grooved, with chamfer
<b>ISO 8741:1997</b>	Grooved pins — Half-length reverse taper grooved
<b>ISO 8742:1997</b>	Grooved pins — One-third-length centre grooved
<b>ISO 8743:1997</b>	Grooved pins — Half-length centre grooved
<b>ISO 8744:1997</b>	Grooved pins — Full-length taper grooved
<b>ISO 8745:1997</b>	Grooved pins — Half-length taper grooved
<b>ISO 8746:1997</b>	Grooved pins with round head
<b>ISO 8747:1997</b>	Grooved pins with countersunk head
<b>ISO 8748:1997</b>	Spring-type straight pins — Coiled, heavy duty
<b>ISO 8750:1997</b>	Spring-type straight pins — Coiled, standard duty
<b>ISO 8751:1997</b>	Spring-type straight pins — Coiled, light duty
<b>ISO 8752:1997</b>	Spring-type straight pins — Slotted, heavy duty
<b>ISO 13337:1997</b>	Spring-type straight pins — Slotted, light duty

### 3.12 Rivets

<b>ISO/R 1051:1969</b>	Rivet shank diameters (diameter range 1 to 36 mm)
------------------------	---